

Maximize efficiency with ITPC
3000/5000/7000 Series
from ₹30999*

Dual Display
Output

Up to **4K**
Resolution

USB Type-C
Support



VESA
Mount

M.2 2280
with **SATA**

 **Windows 11**  **Office 365**



Power Up with 10th/12th Gen
Powerful Processors



ITPC

3000/5000/7000 Series

Processor/ Chipset	Intel® 10th Gen Comet Lake CPU 35W or 65W i3/i5/i7/Pentium/Celeron	Intel® 12th Gen Alder Lake CPU 35W or 65W i3/i5/i7/Pentium/Celeron LGA 1700 Socket
Memory	2 x SODIMM DDR4 2666MHZ	2 x SODIMM DDR4 3200MHZ (Max 64GB)
Storage Interface	M.2 2280mm PCI-E/SATA SSD (M) SATAIII for 2.5" HDD / SSD	1x M.2 2280mm PCI-e NVME Gen3 x4/ SATA SSD (M) 1x SATAIII for 2.5" HDD / SSD
Connectivity	M.2 2230 WiFi/BT slot AC3165 Giga LAN / RTL8111H LAN IC	M.2 2230 WiFi/BT slot AC3165 or AX201 Giga LAN / RTL8125B 2.5GB LAN IC
Front IO	2 x USB3.2 gen.1x1 port 1 x USB3.2 gen.1x1 Type C port 2 Audio Jack (MIC and Line out)	2 x USB3.2 gen.1x1 port 2 x USB3.2 gen.2x1 Type C port 1 x Combo Audio Jack (support CTIA) 1 x MIC
Rear IO	1 x DC-in jack (5.5Ø) 4 x USB2.0 1 x HDMI 2 x DP (1 DP co-lay with D-SUB) 1 x D-SUB 1 x RJ45(Gb) 1 x RS232 (optional) (max 2 concurrent displays)	1 x DC-in jack (5.5Ø) 2 x USB3.2 gen 1x1 Type A 2 x USB2.0 Type A 1 x HDMI (2.0b) 2 x DP (1.4a) 1 x VGA or RS232 (optional) 1 x RJ45(Gb) (max 3 concurrent displays)
Speaker	N/A	1 x MIC & 1 x COMBO Jack (support CTIA)
Additional Features	1.1L DT System Speaker header (optional) ST TPM IC v2.0 on board (optional)	1 x 2W Internal speaker (optional) ST TPM IC v2.0 on board (optional)
OS Support	Windows 11 Linux	Windows 11 Linux
Dimensions(mm)	205(W) x 176(D) x 33(H) mm	205(W) x 176(D) x 33(H) mm 1.1L DT System
Accessory	VESA Mount Adapter(19V 90W) for 35W CPU Adapter(19V 120W) for 65W CPU Stand	VESA Mount Adapter(19V 120W) for 65W CPU Stand

Head Office

#703 1st Floor, No. 677,
13th Cross Rd, 1st Sector,
HSR Layout, Bengaluru,
Karnataka 560102

Sales
sales@itvirt.in
7838950505

Service
contact@itvirt.in
7838940505

